

Contact insert module - HC-M-03-PN-M-F

1417433

ID:1417433

Please be informed that the data shown in this PDF document is generated from our Online Catalog. Please find the complete data in the user documentation. Our General Terms of Use for Downloads are valid.



Contact insert module, number of positions: 3, Socket, Pin, application: Pneumatics, for internal hose diameter of 1.6 / 3 / 4 mm

Commercial Data

Item number	1417433
Packing unit	5 pc
Minimum order quantity	5 pc
Product Key	BF7ACE
Catalog Page	Page 593 (C-2-2019)
GTIN	4055626112947
Weight per Piece (including packing)	5.92 g
Weight per Piece (excluding packing)	5.62 g
Customs tariff number	85389099
Country of origin	PL

Contact insert module - HC-M-03-PN-M-F

1417433

ID:1417433

Technical Data


Notes

General	For HEAVYCON ADVANCE housing type B6 to B24 and HEAVYCON housing type B6 to B48. HEAVYCON HC-M-B...-MF... module carrier frame required, HC-M-PN... pneumatic pins and sockets are not supplied as standard.
General	Connectors may be operated only when there is no load/voltage.
General	The use of guide pins (HC-CST) and sockets (HC-CBU) is recommended to prevent tip collision due to misalignment.

Product properties

Product type	Pneumatic insert, modular
Number of positions	3
Connection profile	3
Application	Pneumatics
Number of module slots	1
Integrated valve	No
Series	HC-M-03-PN

Dimensions

Dimensional drawing	
Width	34.1 mm
Height	27.2 mm
Length	14.6 mm

Mechanical characteristics

Internal diameter of pressure hose connection	1.6 mm
	3 mm
	4 mm
Contact diameter	5.2 mm

Material specifications

Color	light grey
Flammability rating according to UL 94	V0
Contact carrier material	PC
Standards/regulations	PC: Fire protection in rail vehicles - requirement sets R22, R23, and R24 acc. to DIN EN 45545-2 (Risk level HL1 - HL3)

Connector

Insertion/withdrawal cycles	≥ 500
-----------------------------	-------

Contact insert module - HC-M-03-PN-M-F

1417433

ID:1417433

Environmental and real-life conditions

Ambient conditions

Ambient temperature (operation)	-40 °C ... 80 °C
---------------------------------	------------------

Standards and regulations

Testing

Standards/regulations	PC: Fire protection in rail vehicles - requirement sets R22, R23, and R24 acc. to DIN EN 45545-2 (Risk level HL1 - HL3)
-----------------------	---

Mounting


Assembly instructions	To ensure correct use, installation in housing with IP54 protection or better is required
	- Snap the pneumatic contact and module together. Insert the contact into the module from the front - Place the modules assembled with the contacts in the module carrier frame. - The pneumatic tubes are pushed onto the pneumatic contact from the back of the module. The medium-sized module slots and sleeves/coupling housing with straight cable outlet direction are recommended.

Contact insert module - HC-M-03-PN-M-F

1417433

ID:1417433

Drawings



Contact insert module - HC-M-03-PN-M-F

1417433

ID:1417433

Approvals



CSA
Approval ID: 13631



UL Recognized
Approval ID: E118976



EAC
Approval ID: RU C-DE.AI30.B.01102



EAC
Approval ID: RU C-DE.BL08.B.00511

Contact insert module - HC-M-03-PN-M-F

1417433

ID:1417433

Classifications

ECLASS

ECLASS-9.0	27440220
ECLASS-10.0.1	27440220
ECLASS-11.0	27440220

ETIM

ETIM 8.0	EC000438
----------	----------

UNSPSC

UNSPSC 21.0	39121400
-------------	----------

Contact insert module - HC-M-03-PN-M-F

1417433
ID:1417433

Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Contact insert module - HC-M-03-PN-M-F

1417433

ID:1417433

Accessories

Coding element

Coding element - HC-CBU-MOD - 1636130

ID:1636130



Coding socket for coding up to 16 connectors, for HC Modular

Coding element

Coding element - HC-CST-MOD - 1636127

ID:1636127



Coding peg for coding up to 16 connectors, for HC Modular

Contact insert module - HC-M-03-PN-M-F

1417433

ID:1417433

Pneumatic contact

Pneumatic contact - HC-M-PN3-1,60-ST - 1663488

ID:1663488



Pneumatic pin, for HC-M-PN3 module, internal hose diameter of 1.6 mm

Pneumatic contact

Pneumatic contact - HC-M-PN3-3,00-ST - 1663491

ID:1663491



Pneumatic pin, for HC-M-PN3 module, internal hose diameter of 3.0 mm

Contact insert module - HC-M-03-PN-M-F

1417433

ID:1417433

Pneumatic contact

Pneumatic contact - HC-M-PN3-4,00-ST - 1663501

ID:1663501



Pneumatic pin, for HC-M-PN3 module, internal hose diameter of 4.0 mm

Pneumatic contact

Pneumatic contact - HC-M-PN3-1,60-BU - 1663514

ID:1663514



Pneumatic socket, for HC-M-PN3 module, internal hose diameter of 1.6 mm

Contact insert module - HC-M-03-PN-M-F

1417433

ID:1417433

Pneumatic contact

Pneumatic contact - HC-M-PN3-3,00-BU - 1663527

ID:1663527



Pneumatic socket, for HC-M-PN3 module, internal hose diameter of 3.0 mm

Pneumatic contact

Pneumatic contact - HC-M-PN3-4,00-BU - 1663530

ID:1663530



Pneumatic socket, for HC-M-PN3 module, internal hose diameter of 4.0 mm

Contact insert module - HC-M-03-PN-M-F

1417433

ID:1417433

Pneumatic contact

Pneumatic contact - HC-M-PN3-1,60-BU-V - 1663543

ID:1663543



Pneumatic socket with valve, for HC-M-PN3 module, internal hose diameter of 1.6 mm

Pneumatic contact

Pneumatic contact - HC-M-PN3-3,00-BU-V - 1663556

ID:1663556



Pneumatic socket with valve, for HC-M-PN3 module, internal hose diameter of 3.0 mm

Contact insert module - HC-M-03-PN-M-F

1417433

ID:1417433

Pneumatic contact

Pneumatic contact - HC-M-PN3-4,00-BU-V - 1663569

ID:1663569



Pneumatic socket with valve, for HC-M-PN3 module, internal hose diameter of 4.0 mm

Module carrier frame

Module carrier frame - HC-M-B06-MFH-B - 1182085

ID:1182085



Module carrier frame, size: B6, type : for the panel mounting side (a, b, c, ...), 4 mm² ... 6 mm², application: Module carrier frame

Contact insert module - HC-M-03-PN-M-F

1417433

ID:1417433

Module carrier frame

Module carrier frame - HC-M-B10-MFH-B - 1182088

ID:1182088



Module carrier frame, size: B10, type : for the panel mounting side (a, b, c, ...), 4 mm² ... 6 mm², application: Module carrier frame

Module carrier frame

Module carrier frame - HC-M-B16-MFH-B - 1182090

ID:1182090



Module carrier frame, size: B16, type : for the panel mounting side (a, b, c, ...), 4 mm² ... 6 mm², application: Module carrier frame

Contact insert module - HC-M-03-PN-M-F

1417433

ID:1417433

Module carrier frame

Module carrier frame - HC-M-B24-MFH-B - 1182094

ID:1182094

Module carrier frame, size: B24, type : for the panel mounting side (a, b, c, ...), 4 mm² ... 6 mm², application: Module carrier frame



Module carrier frame

Module carrier frame - HC-M-B06-MFH-H - 1182087

ID:1182087

Module carrier frame, size: B6, type : for the sleeve side (A, B, C, ...), 4 mm² ... 6 mm², application: Module carrier frame



Contact insert module - HC-M-03-PN-M-F


1417433

ID:1417433

Module carrier frame

Module carrier frame - HC-M-B10-MFH-H - 1182089

ID:1182089




Module carrier frame, size: B10, type : for the sleeve side (A, B, C, ...), 4 mm² ... 6 mm², application: Module carrier frame

Module carrier frame

Module carrier frame - HC-M-B16-MFH-H - 1182093

ID:1182093



Module carrier frame, size: B16, type : for the sleeve side (A, B, C, ...), 4 mm² ... 6 mm², application: Module carrier frame

Contact insert module - HC-M-03-PN-M-F

1417433

ID:1417433

Module carrier frame

Module carrier frame - HC-M-B24-MFH-H - 1182095

ID:1182095

Module carrier frame, size: B24, type : for the sleeve side (A, B, C, ...), 4 mm² ...
6 mm², application: Module carrier frame

