

# Torque screwdriver - TSD 02 SAC

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid



Torque screwdriver, with preset torque of 0.2 Nm and 4 mm hexagonal drive for M8 connectors

The figure shows the TSD 04 SAC version

## Your advantages

- ✓ Wide range of SAC... nuts for various different applications
- ✓ The TSD-M... adapters can accommodate the various nuts
- ✓ TSD ... SAC torque screwdrivers with a range of preset torques from 0.2 Nm to 2.5 Nm
- ✓ For the TSD-M... torque screwdrivers, the torque can be custom-set

## Key Commercial Data

Packing unit	1 pc
GTIN	 4 046356 014571
GTIN	4046356014571
Weight per Piece (excluding packing)	94.500 g
Custom tariff number	82054000
Country of origin	Czech Republic

## Technical data

### Dimensions

Length (b)	205 mm
Width (a)	37 mm
Blade thickness	0 mm
Blade width	0 mm
Blade height	100 mm

### General

Color	black
Type	Hexagonal SW4

# Torque screwdriver - TSD 02 SAC

## Technical data

### Environmental Product Compliance

California Proposition 65	Further information on California's prop. 65 is available under "Downloads" in the manufacturer's declaration
---------------------------	---

## Classifications

### eCl@ss

eCl@ss 10.0.1	21040417
eCl@ss 11.0	21040417
eCl@ss 4.0	21040400
eCl@ss 4.1	21040400
eCl@ss 5.0	21040400
eCl@ss 5.1	21040400
eCl@ss 6.0	21040400
eCl@ss 7.0	21040417
eCl@ss 9.0	21040417

### ETIM

ETIM 2.0	EC000158
ETIM 3.0	EC000158
ETIM 4.0	EC000158
ETIM 6.0	EC002132
ETIM 7.0	EC002132

### UNSPSC

UNSPSC 6.01	27111701
UNSPSC 7.0901	27111701
UNSPSC 11	27111701
UNSPSC 12.01	27111701
UNSPSC 13.2	27111701

## Approvals

### Approvals

---

Approvals

EAC

---

# Torque screwdriver - TSD 02 SAC

## Approvals

Ex Approvals

---

### Approval details

EAC	
-----	---

## Accessories

Accessories

Screwdriver tools

Tool - SAC BIT M8-D10 - 1208461

Nut for assembling M8 connectors with longitudinal knurl and a knurl diameter of 10 mm, for 4 mm hexagonal drive

---

Tool - SACC BIT M8-D12

Nut for assembling M8 connectors with longitudinal knurl and a knurl diameter of 12 mm, for 4 mm hexagonal drive

---

---